



LANCASTER

WATER TREATMENT

Est. 1942

WHOLE HOUSE PACKAGE

CLEAR-FLO

Prevent Staining & Build-Up

Filters treat water to protect pipes, faucets, water heaters, boilers, and other appliances that require the use of water. As a result, water stains are eliminated, and the water system will remain clear to maintain functionality.

Chemical Free Water Filtration

Utilizing physical filtering media to collect water contaminants rather than using chemicals to alter the contaminants within the water allows the system to provide your home with safe and healthy water.

Space Saving

We understand that homes come in all shapes and sizes. To ensure that we provide you with the best fit for your home, we offer these space saving cartridge filtration options.



**EASY
SET-UP**



**SIMPLIFIED
MAINTENANCE**



**BROAD
SOLUTION RANGE**



**CONTAMINANT
REMOVAL**

CLEAR-FLO WHOLE HOUSE FILTER

OUR CLEAR-FLO WHOLE HOUSE FILTER CAN HANDLE LARGE CAPACITY OR HEAVY-DUTY SEDIMENT FILTRATION REQUIREMENTS, SUITABLE FOR RESIDENTIAL AND COMMERCIAL APPLICATIONS.

HOW IT WORKS:

1. Untreated water enters the Clear-Flo Whole House Filter Housing.
2. The water flows through the melt-blow polypropylene cartridge which captures suspended solids.
3. Treated water enters your home free of fixture clogging sediment.
4. The Clear-Flo Whole House Filter continuously removes contaminants to incoming water while properly maintained.



APPLICATIONS:

- Ultraviolet pre-filtration
- General sediment filtration
- Protection from public water deterioration and flushing

| MODEL NUMBER | SERVICE FLOW RATE (GPM) | PIPE SIZE (IN.) | DIMENSIONS HxW (IN.) | MICRON | TREATMENT |
|--------------|-------------------------|-----------------|----------------------|--------|--|
| 410-WH-5-P | 18 | 1 | 15.35 x 7.48 | 5 | Removes dirt, silica, and most suspended mater |

*Dimensions for estimating purposes

** Package includes wrench, bracket, and lubrication kit

Operating Parameters:

| | |
|----------------------|---|
| SERVICE TIME | Avg. 6 mths. – Cartridge, Max. 5yrs – Housing Sump |
| TEMPERATURE | Min. 39.2°F - Max. 113°F |
| PRESSURE | Max. 120 PSI |
| OTHER CONSIDERATIONS | Other equipment may be needed based on water quality. |